



SB-1

Single gang adjustable electrical box for use with nonmetallic sheathed cable

Mounting Description: 2 Screws

Box Type: Wall - Switch/Receptacle

Box Features: Adjustable box (SLIDERBOX®), Screws

Installation Type: New Work, Old Work

Height: 3-3/4 in

Width: 2-5/16 in

Depth: 3-9/16 in

Volume: 23 cu in

Number of Gangs: 1

Product Info

Brand: SLIDERBOX

UPC: 85339945000

UNSPSC: 39121308

Carton Quantity: 48

Carton Weight: 14 lbs

Country of Origin: United States of America

Color: Beige

Fire Classification: Fire Test of Building Construction Materials ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less Shall be separated by a horizontal distance of not less than 24 inches **Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less** Distance between boxes must be 4-1/2 feet from one another *Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

Patents: U.S. Patent No. 7,855,338

Material: Polyvinyl Chloride

Additional Materials: Carbon steel fasteners, Polycarbonate adjustable mounting plate

Features:

Molded-in splined device holes, adjustable slider plate for additional wall substrate thickness, rectangular exterior for easy cut-in, leveling ribs, offset gauge marks

Application:

New and old work residential construction 2 HR fire resistive walls and ceilings

Standards:

ANSI / UL 514C: [File No. E30594](#)

