



## SB-1

Single gang adjustable electrical box for use with nonmetallic sheathed cable

**Mounting Description:** 2 Screws

**Box Type:** Wall - Switch/Receptacle

**Box Features:** Adjustable box (SLIDERBOX®), Screws

**Installation Type:** New Work, Old Work

**Height:** 3-3/4 in

**Width:** 2-5/16 in

**Depth:** 3-9/16 in

**Volume:** 23 cu in

**Number of Gangs:** 1

## Product Info

**Brand:** SLIDERBOX

**UPC:** 85339945000

**UNSPSC:** 39121308

**Carton Quantity:** 48

**Carton Weight:** 14 lbs

**Country of Origin:** United States of America

**Color:** Beige

**Fire Classification:** Fire Test of Building Construction Materials ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

**Fire Resistance Classification in Wall Assemblies 2-Hours or less** Shall be separated by a horizontal distance of not less than 24 inches **Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less** Distance between boxes must be 4-1/2 feet from one another *Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

**Patents:** U.S. Patent No. 7,855,338

**Material:** Polyvinyl Chloride

**Additional Materials:** Carbon steel fasteners, Polycarbonate adjustable mounting plate

## Features:

Molded-in splined device holes, adjustable slider plate for additional wall substrate thickness, rectangular exterior for easy cut-in, leveling ribs, offset gauge marks

## Application:

New and old work residential construction 2 HR fire resistive walls and ceilings

## Standards:

ANSI / UL 514C: [File No. E30594](#)

