



Product Info

Brand: fiberglassBOX

UPC: 85339244219

UNSPSC: 39121308

Carton Weight: 32 lbs

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

Additional Materials: Carbon steel fasteners

1096-SS

Single gang electrical box for use with nonmetallic sheathed cable

Carton Quantity: 100

Closure Type:

Mounting Description: Steel stud screws for use with non-load bearing studs 22 gauge or lighter

Box Type: Wall - Switch/Receptacle

Box Features: Screws

Installation Type: New Work

Height: 3-13/16 in

Width: 2-1/4 in

Depth: 3 in

Volume: 18 cu in

Number of Gangs: 1

Features:

Machine tapped device holes, offset gauge marks, leveling ribs, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

Application:

New work residential construction – steel or wood studs 2 HR fire resistive walls & ceilings

Standards:

ANSI / UL 514C: [File No. E30594](#)



LISTED

Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 ½ inches

Note: For more details please refer to the UL fire resistive

directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)
