



9318

Single gang electrical box for use with nonmetallic sheathed cable

Closure Type:

Mounting Description: Surface mount

Box Type: Wall - Switch/Receptacle

Box Features:

Installation Type: New Work, Old Work

Height: 4-3/16 in

Width: 2-1/4 in

Depth: 2 in

Volume: 12.5 cu in

Number of Gangs: 1

Product Info

Brand: fiberglassBOX

UPC: 85339101406

UNSPSC: 39121308

Carton Quantity: 100

Carton Weight: 28 lbs

Country of Origin: United States of America

Color: Off white

Fire Classification: **Fire Test of Building Construction Materials** ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C **Fire Resistance Classification in Wall Assemblies 2-Hours or less** Shall be separated by a horizontal distance of not less than 3 inches **Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less** Distance between boxes in adjacent cavities may be reduced to 5 ½ inches Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

Material: Fiberglass reinforced polyester

Additional Materials:

Features:

Machine tapped device holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

Application:

Surface mounted box with side and bottom romex cable openings

Standards:

ANSI / UL 514C: [File No. E30594](#)

