



**ALLIED  
MOULDED  
PRODUCTS, Inc.**

**419-636-4217  
222 N. Union St.  
Bryan, OH 43506**



## 9318

Single gang electrical box for use with nonmetallic sheathed cable

**Closure Type:**

**Mounting Description:** Surface mount

**Box Type:** Wall - Switch/Receptacle

**Box Features:**

**Installation Type:** New Work, Old Work

**Height:** 4-3/16 in

**Width:** 2-1/4 in

**Depth:** 2 in

**Volume:** 12.5 cu in

**Number of Gangs:** 1

## Product Info

**Brand:** fiberglassBOX

**UPC:** 85339101406

**UNSPSC:** 39121308

**Carton Quantity:** 100

**Carton Weight:** 28 lbs

**Country of Origin:** United States of America

**Color:** Off white

**Fire Classification: Fire Test of Building Construction Materials** ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C **Fire Resistance Classification in Wall Assemblies 2-Hours or less** Shall be separated by a horizontal distance of not less than 3 inches **Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less** Distance between boxes in adjacent cavities may be reduced to 5 ½ inches Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

**Material:** Fiberglass reinforced polyester

**Additional Materials:**

## Features:

Machine tapped device holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

## Application:

Surface mounted box with side and bottom romex cable openings

## Standards:

ANSI / UL 514C: [File No. E30594](#)

