



P-108E

Single gang electrical box for use with nonmetallic sheathed cable Box Type: Wall - Switch/Receptacle Box Features: Nonmetal ears Installation Type: Old Work Height: 3-3/4 in Width: 2-5/16 in Depth: 1-1/4 in Volume: 8 cu in Number of Gangs: 1

Product Info

Brand: flexBOX

UPC: 85339249177

UNSPSC: 39121308

Carton Quantity: 24

Carton Weight: 3 lbs

Country of Origin: United States of America

Color: Black

Fire Classification: Fire Test of Building Construction Materials ANSI / UL 263: <u>File No. CEYY.R9379</u> (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C **Fire Resistance Classification in Wall Assemblies 2-Hours or less** Shall be separated by a horizontal distance of not less than 24 inches **Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less** Distance between boxes must be 4-½ feet from one another *Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance*)

Material: Polyvinyl Chloride

Features:

Molded-in spline device holes, rectangular exterior for easy cut-in

Application:

Old work residential construction 2 HR fire resistive walls

Standards:

ANSI / UL 514C: File No. E30594

×