



## Product Info

**Brand:** flexBOX

**UPC:** 85339249160

**UNSPSC:** 39121308

**Carton Quantity:** 48

**Carton Weight:** 10 lbs

**Country of Origin:** United States of America

**Color:** Black

**Fire Classification:** Fire Test of Building Construction Materials ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C  
**Fire Resistance Classification in Wall Assemblies 2-Hours or less** Shall be separated by a horizontal distance of not less than 24 inches  
**Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less** Distance between boxes must be 4-½ feet from one another Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

**Material:** Polyvinyl Chloride

**Additional Materials:** Galvanized snap in bracket

## P-181H

Single gang electrical box for use with nonmetallic sheathed cable

**Closure Type:**

**Mounting Description:** Molded-in side mount hanger bracket

**Box Type:** Wall - Switch/Receptacle

**Box Features:** "HL" hanger

**Installation Type:** New Work

**Height:** 3-3/4 in

**Width:** 2-5/16 in

**Depth:** 2-3/4 in

**Volume:** 18 cu in

**Number of Gangs:** 1

## Features:

Molded-in splined device holes, leveling ribs

## Application:

New work residential construction 2 HR fire resistive walls & ceilings

## Standards:

ANSI / UL 514C: [File No. E30594](#)

