



ALLIED
MOULDED
PRODUCTS, Inc.

419-636-4217
222 N. Union St.
Bryan, OH 43506



P-241HQT

Single gang electrical box for use with nonmetallic sheathed cable

Closure Type:

Mounting Description: Molded-in side mount hanger bracket

Box Type: Wall - Switch/Receptacle

Box Features: "HL" hanger

Installation Type: New Work

Height: 3-3/4 in

Width: 2-5/16 in

Depth: 3-9/16 in

Volume: 24 cu in

Number of Gangs: 1

Product Info

Brand: flexBOX

UPC: 85339249085

UNSPSC: 39121308

Carton Quantity: 50

Carton Weight: 12 lbs

Country of Origin: United States of America

Color: Black

Fire Classification: Fire Test of Building Construction Materials ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less Shall be separated by a horizontal distance of not less than 24 inches **Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less** Distance between boxes must be 4-½ feet from one another *Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

Material: Polyvinyl Chloride

Additional Materials: Galvanized snap in bracket

Features:

Quick Thread device holes, leveling ribs

Application:

New work residential construction 2 HR fire resistive walls & ceilings

Standards:

ANSI / UL 514C: [File No. E30594](#)

