



## P-3520W

Three gang electrical box for use with nonmetallic sheathed cable

**Mounting Description:** Metal wing brackets/nonmetal ears wall compression

**Box Type:** Wall - Switch/Receptacle

**Box Features:** Nonmetal ears, Wing bracket

**Installation Type:** Old Work

**Height:** 3-11/16 in

**Width:** 5-15/16 in

**Depth:** 3-3/8 in

**Volume:** 55 cu in

**Number of Gangs:** 3

## Product Info

**Brand:** flexBOX

**UPC:** 85339332015

**UNSPSC:** 39121308

**Carton Quantity:** 12

**Carton Weight:** 6 lbs

**Country of Origin:** United States of America

**Color:** Black

**Fire Classification: Fire Test of Building Construction Materials** ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.) *Note: Products must also be certified to: ANSI / UL 514C* **Fire Resistance Classification in Wall Assemblies 2-Hours or less** Shall be separated by a horizontal distance of not less than 24 inches *Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

**Patents:** U.S. Patent No. 6,365,831 B1

**Material:** Polycarbonate

**Additional Materials:** Galvanized steel brackets and plated carbon steel fasteners

## Features:

Molded-in spline device holes, slot provision for low voltage divider, rectangular exterior for easy cut-in

## Application:

Old work residential construction 2 HR fire resistive walls

## Standards:

ANSI / UL 514C: [File No. E30594](#)

