ISSUE DATE: 3.99 101.22 -6.72 170.69]→ .56[14.30]— .88 22.23 -OPTIONAL BACK PANEL SHOWN 0.100 [2.54mm] TH'K- ALUMINUM 0.075 [1.91mm] TH'K- WHITE STEEL & GALVANNEALED 0.125 [3.18mm] TH'K- FIBERGLASS (2) POLYCARBONATE FLANGES (GLUED) .10 [2.54] 6.50 165.10 7.63 [193.79] (4) EACH #10-32 BRASS-INSERTS, AND STAINLESS STEEL FLANGE AND 4.10 104.14 **BACK VIEW FEET SCREWS** 6.75 [171.44] 5.18 131.47 6.88 174.74 STAINLESS STEEL SLOT HINGE PIN MAX DIST (8) R.162 [4.102] **SLOT** DIST FRONT VIEW WITH COVER REMOVED AND BACK PANEL DISPLAYED CLOSED CELL-NEOPRENE 4.00 [101.60] NONMETALLIC → 4.81 [122.24] < LOCKABLE SNAP LATCH LOCATED ON CENTER **GASKET** 6.04 [153.40] - .13 [3.30] 4.81 [122.24] 4.25 [107.95] -(4) EACH #10-32 BRASS INSERTS AND PLATED 4.25 [107.95] **CARBON STEEL SCREWS** 6.26 [158.99] R ALLIED MOULDED PRODUCTS BRYAN, OHIO The Original Fiber Glass Outlet Box AMU Ultraline MATERIAL:
BOX- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER
COVER- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER **CONFIDENTIAL** AMU664CCNLF THIS MATERIAL IS OWNED BY THE ALLIED MOULDED PRODUCTS COMPANY, IS DISCLOSED IN CONFIDENCE AND IS NOT TO BE REPRODUCED OR DISTRIBUTED

CLEAR COVER AND WINDOWS- POLYCARBONATE

WITHOUT PRIOR WRITTEN PERMISSION FROM ALLIED MOULDED PRODUCTS.