ISSUE DATE: .56 [14.30] - 6.72 [170.69] -3.99 [101.22] .76 [19.41] -> OPTIONAL BACK PANEL SHOWN 0.100 [2.54mm] TH'K- ALUMINUM В 0.075 [1.91mm] TH'K- WHITE STEEL & GALVANNEALED 0.125 [3.18mm] TH'K- FIBERGLASS -(2) POLYCARBONATE FLANGES (GLUED) 6.50 [165.10] .10 [2.54] **BACK VIEW** 3.50 [88.90] 7.63 [193.79] (4) EACH #10-32 BRASS INSERTS, AND STAINLESS 3.99 [101.32] STÉEL FLANGE AND **FEET SCREWS** 6.75 [171.44] 5.18 [131.47] 🚤 SLOT 6.88 [174.74] 3.50 [88.90] (8) R.162 [4.102] MAX DIST STAINLESS STEEL HINGE PIN **SLOT** -(2) EACH #10-32 BRASS INSERTS AND STAINLESS STEEL CAPTIVE COVER SCREWS DIST FRONT VIEW WITH COVER REMOVED AND BACK PANEL DISPLAYED CLOSED CELL-4.00 [101.60] NEOPRENE → 4.81 [122.24] <del><</del> **GASKET** - .13 [3.30] 6.04 [153.40] 4.81 [122.24] 4.25 [107.95] (4) EACH #10-32 BRASS INSERTS AND PLATED 4.25 [107.95] **CARBON STEEL SCREWS** 6.26 [158.99] R ALLIED MOULDED PRODUCTS BRYAN, OHIO The Original Fiber Glass Outlet Box AMU Ultraline MATERIAL:
BOX- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER
COVER- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER **CONFIDENTIAL** AMU664HWF THIS MATERIAL IS OWNED BY THE ALLIED MOULDED PRODUCTS COMPANY, IS DISCLOSED IN CONFIDENCE AND IS NOT TO BE REPRODUCED OR DISTRIBUTED

CLEAR COVER AND WINDOWS- POLYCARBONATE

WITHOUT PRIOR WRITTEN PERMISSION FROM ALLIED MOULDED PRODUCTS.